# **Bam-Product Specification**



#### Ram

Big Greenville Rope-play house Bam with an elevenfold suspended spatial net (rope diameter Ø18mm) and bamboo panels. Equipped with the AstemTT net tensioning system.

Revision: March 2016

## Bam - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Greenville 90.270.000 5+ 1.99 m (6'-7") 3.98 m x 3.80 m x 3.26 m (13'-1" x 12'-6" x 10'-9") 7.63 m x 7.46 m 7.63 m x 7.46 m (25'-1" x 24'-6")

44.61 m<sup>2</sup>

44.68 m<sup>2</sup> (481 sf)

Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee: Gross weight Certificate according to DIN EN 1176: 3 8 hours 1.8 m x 1.5 m x 0.04 m (16'-1" x 2'-12" x 1'-12") 60 kg (132.3 lbs) 4.0 m³ (141.3 ft³) Lifelong 1000 kg (2205 lbs) No.: Z1A 13 06 10256 094 TÜV Product Service




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178



# **Bam-Product Specification**



Revision: March 2016

### Technical Data.

The following text can also be used for tenders.

#### Tube framework:

A combination of straight and bended stainless steel Frameworx-®tubes,  $\varnothing$  60,3 m(2 3/8"), material AlSI304 (DIN 1.4301). The tubes are connected to build a space framework with a triangular footprint.

#### Nodes:

Frameworx-aluminum ball connectors; Ø 250 mm (9'-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

## Ropes:

U-Rope®-round strand ropes with galvanized and covered wires, external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene). Rope-diameter Ø 18mm (11/16").

### Special netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings, joint-ferrule, connecting-clamps and barrel-ferrule (no plastic connections); in situreplaceable rope strands.

### Bamboo panels:

Bamboo strips 90 mm, (3'-1/2") mounted at a particle board made from HDPE, 19 mm (3/4") thickness, rounded edges, mounted with aluminum plate clamps to the tubes of the framework.





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

