

CombiNation – The clever combination of all play systems Berliner Seilfabrik offers an endless variety of play systems. But, that's not all: Since all play equipments consist of the same basic modules, the various play systems can easily be combined with each other.

The following play systems are only examples - use the countless design options to create your own unique play combination!

Cambridge.03 - At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):


Minimum space required DIN EN 1176: Minimum space required ASTM 1487: CombiNation 95.170.448 5+ 2.00 m (6'-7") 21.7 m x 15.3 m x 5.8 m (71'-0" x 50'-2" x 19'-1") 24.7 m x 18.3 m 25.8 m x 19.0 m (84'-6" x 62'-2") 332.0 m² 366.1 m² (3,940.7 sf) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee: 65 pc. 18.3 m³ (646.3 ft³) 4 22 hours 0.8 m x 0.8 m x 8.7 m (2'-7" x 2'-7" x 28'-7") 300 kg (661.4 lbs) Upon request Lifelong



Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178





Technical Data. The following text can also be used for tenders.

- ٠
- Terranos® netscape Hand-over-hand ladder and loop-rope ٠
- Space cell ٠
- Chin-up bars •
- Quadropolis towers with access nets ٠
- Tunnel slide ٠
- Transfer bridge •





Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

Terranos® netscape:

Steel posts Jan:

Steel pipes \varnothing 133 mm (5 ¼") with rounded cast aluminum post top, minimum wall thickness 7.1mm (1/4"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

Frox-rope connections:

All connections for Terranos-rope elements in Terranos-grid dimension 3000mm (standard linear dimension; 9'- 10 1/8'') or 4243mm (diagonal dimension; 13'- 11-1/16'') are equipped with Frox-Rope connections that are fully enclosed and free from any entrapment risks.

Terranos clamps:

Two-part cast aluminum clamps for the height-adjustable connection between rope elements or steel pipes to Terranos steel posts.

Ropes:

U-Rope-round strand ropes with galvanized steel cores, \varnothing 16mm (5/8") – unless otherwise noted; external strands are covered with non-abrasive UV-resistant Polyester-yarn.

Planar netting:

Rope crossing points localized by durable, drop forged aluminumballknots (no plastic).

Folded net:

A double-triangular net, mesh size 300x300mm (11-13/16"x11-13/16"), fastened at four points.

Trapeze net:

A trapezoid planar net with 6m² (appr. 65 square foot), mesh size 300x300mm (11-13/16"x11-13/16"), fastened at four points.

Hand-over-hand-ladder:

Width 290mm (11-7/16"), distance between rungs 250-300mm (9-13/16" to 11-13/16"), rungs comprised of American ash (alternatively Nylon 6.6.).

Hand-over-hand rope loops:

All ropes Ø 21mm (13/16"), length per loop 300 – 350mm (11-13/16" - 13 $\frac{3}{4}$ ").

Space cell:

Twelvefold suspended 3d-net cell, all suspension cables connected to steel posts with cast aluminum Terranos clamps.

Chin-up-bars:

Comprises of stainless steel pipe 40x5.0mm (1-9/16" x 3/16") AISI304 (DIN 1.4301).





Technical Data.



Berliner Selfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

Quadropolis towers:

Members:

Frameworx-steel pipes, \varnothing 60.3 mm (2 3/8"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

Nodes:

Frameworx-aluminum ball connectors, \varnothing 250mm (9-13/16''); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system, securely closed with durable ebonite caps.

Panels:

HDPE-panel, thickness 19mm (3/4"), panel connected to steel pipes (for more details, see members) with cast aluminum panel clamps.

Steel supports:

Uprights comprised of steel pipes \varnothing 133 mm (5 ¼") with rounded cast aluminum post tops, minimum wall thickness 7.1mm (1/4"); horizontal members comprised of Frameworx-steel pipes, \varnothing 60.3 mm (2 3/8"); All connections to upright posts are with cast aluminum Terranos clamps; anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

Tube Slides:

Attached slides comprised of stainless steel AISI304 (DIN 1.4301).

Transfer bridge:

Steel posts Jan:

Steel pipes \varnothing 133 mm (5 ¼'') with rounded cast aluminum post top, minimum wall thickness 7.1mm (1/4''); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

Transfer bridge:

Small meshed Net bridge with double in situ-replaceable square rungs; rungs comprised of stainless steel profile AISI304 (DIN 1.4301) with aluminum end caps.

Transfer station:

Three uprights of steel pipe, \emptyset 133 mm (5 ¼"), horizontal members comprised of Frameworx-steel pipes, \emptyset 60.3 mm (2 3/8"); with two triangular platform panels (for more, see panels), one handle as transfer support is connected to one post. All connections to upright posts with cast aluminum Terranos clamps; anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.



Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178