

Cloud 9 – Product Specification



HodgePodge – A variety of study and durable sport and play elements

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities.

Climbing trees, a Wasp's nest, Volleyball nets for sporting activities, cable rides for fun and excitement.

At a glance.

Product Family:	HodgePodge	Number of Foundations:	2 pc.
Item Number:	97.100.025	Concrete Volume C20/C25:	0.7 m³ (24.7 ft³)
Children's Age:	3+	Number of skilled installers required:	2
Fall Height (DIN EN 1176):	1.80 m (5'-11")	Installation Time without foundation:	2 hours
Length x Width x Height:	3.2 m x 1.2 m x 2.0 m (10'-5" x 4'-0" x 6'-8")	Dimensions of largest part:	Ø 0.1 x 3.1 m (0'-4" x 10'-2")
Protective Surfacing Area (DIN EN 1176):	6.2 m x 6.4 m	Weight of heaviest part:	70 kg (154.3 lbs)
Protective Surfacing Area (ASTM 1487):	6.8 m x 8.1 m (22'-4" x 26'-7")	Shipping Volume:	1.8 m³ (63.6 ft³)
Minimum space required DIN EN 1176:	26.6 m²	Spare part guarantee:	Lifelong
Minimum space required ASTM 1487:	31.0 m² (333.7 sf)	Certificate according to EN 1176:	No.: Z2.16.01.10256.259 TÜV Product Service


Berliner
 Berliner Seilfabrik
 Play Equipment Corporation
 96 Brookfield Oaks Drive, Suite 140
 Greenville, SC 29607

T + 1 864 627 1092
 F + 1 864 627 1178

www.berliner-playequipment.com
info@berliner-seilfabrik.com

Cloud 9 – Product Specification



Technical Data.

The following text can also be used for tenders.

Steel posts Jan:

Steel pipes \varnothing 133 mm (5 1/4") with rounded cast aluminum post top, minimum wall thickness 7.1mm (1/4"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

Nodes:

Framework-aluminum ball connectors; \varnothing 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

Seat:

Galvanized steel ring covered with shock-absorbing material and wrapped with fiber rope (\varnothing 20 mm); coil: 115 mm x 95 mm); tight-knit net made of Usacord rope (16 mm) is hung into the ring

Ropes:

U-Rope-round strand ropes with steel cores, \varnothing 16mm (5/8") – unless otherwise noted; with galvanized wires, external strands covered with non-abrasive UV-resistant Polyester-yarn.

t.


Berliner
Berliner Seilfabrik
Play Equipment Corporation
96 Brookfield Oaks Drive, Suite 140
Greenville, SC 29607

T + 1 864 627 1092
F + 1 864 627 1178

www.berliner-playequipment.com
info@berliner-seilfabrik.com

