# **Double Cloud 9 - Product Specification**



### HodgePodge - A variety of study and durable sport and play elements

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities.

Climbing trees, a Wasp's nest, Volleyball nets for sporting activities, cable rides for fun and excitement.

### Double Cloud 9 - At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

HodgePodge 95.171.311 3+ 1.80 m (5'-11")

6.2 m x 1.2 m x 2.0 m (20'-4" x 3'-11" x 6'-8") 9.2 m x 6.4 m 9.9 m x 8.1 m (32'-4" x 26'-7")

59,87 m<sup>2</sup> 59,96 m<sup>2</sup> Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Revision: September 2016

Certificate according to EN 1176:

3 pc.

1,03 m<sup>3</sup> (36.35 ft<sup>3</sup>)

2 4 hours Ø0,14x3,1 m (0'-4" x 10'-2") 70 kg (154.3lbs) Upon request Lifelong

No.: Z2.16.01.10256.259 TÜV Product Service



Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

# **Double Cloud 9 - Product Specification**



### **Technical Data.**

The following text can also be used for tenders.

## Steel posts Jan:

Steel pipes  $\varnothing$  133 mm (5 ¼") with rounded cast aluminum post top, minimum wall thickness 7.1mm (1/4"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

#### Nodes:

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

### Seat:

Galvanized steel ring covered with shock-absorbing material and wrapped with fiber rope (Ø 20 mm); coil: 115 mm x 95 mm); tight-knit net made of Usacord rope (16 mm) is hung into the ring

#### Ropes

Revision: September 2016

U-Rope-round strand ropes with steel cores,  $\varnothing$  16mm (5/8") – unless otherwise noted; with galvanized wires, external strands covered with non-abrasive UV-resistant Polyester-yarn.





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178