Jupiter - Product Specification



Univers - Classics among rope playground equipment

Net structures offer hours of fun and adventure on several levels – climbing and swinging, up and down, horizontally and vertically – space on earth.

The original spatial nets: Born over 40 years ago as a play concept, continuously further developed in form and detail, still popular even after several generations.

Revision: March 2016

Jupiter – at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487: Univers 90.100.040 5+ 1.49 m 4.4 m x 4.4 m x 4.5 m (14'-5" x 14'-5" x 14'-9") 7.4 m x 7.4 m

7.4 m x 7.4 m 8.,1 m x 8.1 m (26'-7" x 26'-7") 52.1 m²

61,2 m² (658.8 sf)

Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation:

Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Certificate according to DIN EN 1176:

4 pc.

1.5 m³ (53.0 ft³)

2 5 hours Ø 0.1 m x 1.8 m (Ø4" x 5'-11") 140 kg (308.7 lbs) 2.5 m³ (26.9 ft³) Lifelong


No.: Z2 16 01 10256 241 TÜV Product Service




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

Jupiter - Product Specification





Revision: March 2016

Technical Data.

The following text can also be used for tenders.

Tube framework:

Frameworx-steel tubes, Ø 60.3 mm (2 3/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Nodes:

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8")

Spatial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required)





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178