Roo S.01 - Product Specification





Spooky Rookies - Haunted Playhouses for Toddlers

Spooky Rookies promote physical development. During climbing, sliding and romping in the many different playhouses, toddlers are able to test their skills.

It is possible to combine the playhouses' shape, size and colours. A stepladder, ramp or slide offer further constructive options. The diversity of Spooky Rookies are also enjoyed by four ghosts. They represent a colour concept in each case and live in the playhouses. Do not be afraid, the ghosts are pleased about every guest.

Roo S.01 - At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area(DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Spooky Rookies 90.295.500.1 3+

0.45 m (1'-6") 1.6 m x 2.6 m x 1.7 m (5'-3" x 8'-7" x 5'-7") 4.6 m x 5.6 m 5.2 m x 6.3 m

(17'-1" x 20'-9") 21.87 m² 27.79 m² (299.13 ft²) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Revision: February 2017

Certificate according to DIN EN1176:

8 pc.

0.8 m3 (28.3 ft3)

4 hours 1.2 m x 1.2 m (3'-12" x 3'-12") 45 kg (99.3 lbs)

Upon request Lifelong


No.: Z2 17 01 10256 240 TÜV Product Service



Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

Roo S.01 - Product Specification



scale 1:100



Technical Data.

The following text can also be used for tenders.

- 1 haunted house
- 1 ramp
- 1 stepladder

Posts:

Steel pipes Ø 101.6 mm (0'-4''): wall thickness 4 mm (0'-1'') with a round cast aluminum post top; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Cross tubes - stainless steel Frameworx-®tubes, Ø 48 mm (0'-2")

Nodes:

Frameworx-®aluminum ball connectors, \varnothing 200 mm (0'-8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-caps

Panels/Ramp:

HDPE-panel (roof and walls), thickness 19 mm (3/4"), panel connected to steel pipes (for more details, see members) with cast aluminum panel clamps; non-skid HPL-panel (bottom and ramp), thickness 19 mm (3/4")

Connections:

Number of mechanical components as less as possible; all bolts and nuts exposing permanently to the weather consist of stainless steel

Stepladder:

Revision: February 2017

Non-skid HPL-tiles (steps), thickness 19 mm (3/4 $^{\prime\prime}$); curved stainless steel handrails



Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

