# Spaceball M - Product Specification



# Univers - Classics among rope playground equipment

Net structures offer hours of fun and adventure on several levels – climbing and swinging, up and down, horizontally and vertically – space on earth.

The original spatial nets: Born over 40 years ago as a play concept, continuously further developed in form and detail, still popular even after several generations.

## Spaceball M - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

Univers 90.100.041 5+ 1.49 m (4'-11") 4.4 m x 4.4 m x 3.7 m

(14'-5" x 14'-5" x 12'-0") 7.4 m x 7.4 m 8.1 m x 8.1 m (26'-5" x 26'-5") 40.8 m<sup>2</sup>

40.8 m<sup>2</sup> 48.7 m<sup>2</sup> (524.2 sf) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation:

Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Revision: March 2016

Certificate according to DIN EN 1176:

4 pc. 1.5 m³ (53.0 ft³)

Lifelong

2 6 hours Ø 0.1 m x 1.8 m (0'-4" x 5'-11") 130 kg (286.6 lbs) 2.7 m³ (95.3 ft³)


No.: **Z2** 16 01 10256 246 TÜV Product Service




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

# Spaceball M - Product Specification





Revision: March 2016

# Technical Data.

The following text can also be used for tenders.

### Tube framework:

Frameworx-steel tubes, Ø 60.3 mm (2 3/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

### Nodes:

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

## Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter  $\emptyset$  16 mm (5/8")

#### Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required)





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178