Shack1.01– Product Specification



Shack1.01

Shack1, with a platform height of 1.5 m is the smaller one of the two play huts. In this variant, the "witch's house" distinguishes itself through it high transparency. The two different entrances can be climbed into using the slanted net ascent as well as a climbing rope with rubber cylinders that function as a climbing support. A special property of Shack1 are the posts that are slanted outwards.

Shack1.01 - at a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487: Woodville 90.224.010.1 3+ 1.5 m (5'-0") 5.0 m x 2.0 m x 3.7 m (16'-4" x 6'-8" x 12'-4") 8.5 m x 5.1 m 8.7 m x 5.7 m (28'-5" x 18'-8") 32.7 m² 40.8 m² (440 sf) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee: Gross weight 2 pc. 1.5 m³ (53 ft³) 3 12 hours 3.2 m x 0.8 m x 0.2 m (10'-6" x 2'-8" x 0'-8") 90 kg (199 lbs) m³ (ft³) Lifelong kg (lbs)



Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178


www.berliner-playequipment.com info@berliner-seilfabrik.com





Revision: June 2017

Shack1.01-Product Specification



Technical Data.

The following text can also be used for tenders.

Wood:

Post tops made of larch glued laminated timber, wall panels and partly platform made of durable robinia wood.

Steel posts :

Terranos posts , Ø 133 mm (5 ¼''); wall thickness 7.1 mm (9/32"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

Tubes:

Straight stainless steel Frameworx-®tubes, Ø 60.3 mm (2 3/8").

Platform:

HPL-platform; thickness 19 mm (3/4"); connected with cast aluminum panel clamps to the steel pipes.

Balls:

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16''); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating a post connection system; securely closed with durable EPDM- caps. The construction prevents the direct contact of the wooden posts with the ground.

Terranos clamps:

Two-part cast aluminium connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos steel posts; anticorrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

Roof, window and door openings:

Shape Milled HDPE panels, 19 mm thick, grained surface, all edges around milled; fixed with cast aluminum clamps to the respective tubes in the main scaffolding.

Access net:

Rope Ø 16mm (5/8"); mesh size minimum 250 x 250 mm (9-4/5"); rope crossing points localized by durable, drop forged aluminum ballknots (no plastic). Stainless steel chain and foundation plates.

Climbing rope:

Rope Ø 21 mm (53/64"); with durable ebonite cylinders; distance between cylinders approx. 300 mm (11-13/16"); ebonite cylinders are fixed to the rope with aluminum ferrules. Stainless steel chain and foundation plate.

Attached slide:

Straight box slide made of stainless steel; the cheeks are welded with stainless steel handrails; afterwards smoothed and polished.





Play Equipment Corporation 96 Brookfield Oaks Drive, Suite Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

www.berliner-playequipment.com info@berliner-seilfabrik.com

