

SpooRoo Combi.03 – Product Specification



Spooky Rookies – Haunted Playhouses for Toddlers

Spooky Rookies promote physical development. During climbing, sliding and romping in the many different playhouses, toddlers are able to test their skills.

It is possible to combine the playhouses' shape, size and colours. A stepladder, ramp or slide offer further constructive options. The diversity of Spooky Rookies are also enjoyed by four ghosts. They represent a colour concept in each case and live in the playhouses. Do not be afraid, the ghosts are pleased about every guest

SpooRoo Combi.03 – At a glance.

Product Family:	Spooky Rookies	Number of Foundations:	12 pc.
Item Number:	90.296.003	Concrete Volume C20/C25:	1.3 m³ (45.91 ft³)
Children's Age:	3+	Number of skilled installers required:	2
Fall Height (DIN EN 1176):	0.90 m (3'-0")	Installation Time without foundation:	9 hours
Length x Width x Height:	2.3 m x 6.9 m x 2.2 m (7'-7" x 22'-8" x 7'-3")	Dimensions of largest part:	2.6 m x 1.3 m x 0.6 m (8'-7" x 4'-4" x 1'-12")
Protective Surfacing Area(DIN EN 1176):	5.3 m x 10.5 m	Weight of heaviest part:	55 kg (121.3 lbs)
Protective Surfacing Area (ASTM 1487):	6.0 m x 10.6 m (19'-9" x 34'-10")	Shipping Volume:	Upon request
Minimum space required DIN EN 1176:	39.94 m²	Spare part guarantee:	Lifelong
Minimum space required ASTM 1487:	46.17 m² (496.97 ft²)	Certificate according to DIN EN 1176:	No.: Z2 17 01 10256 240 TÜV Product Service





Berliner

Berliner Seilfabrik
Play Equipment Corporation
96 Brookfield Oaks Drive, Suite 140
Greenville, SC 29607

T + 1 864 627 1092
F + 1 864 627 1178

www.berliner-playequipment.com
info@berliner-seilfabrik.com

SpooRoo Combi.03 – Product Specification



scale 1:200



Technical Data.

The following text can also be used for tenders.

- 1 haunted house Spoo S
- 1 ramp
- 1 stepladder
- 1 haunted house Roo M
- 1 slide
- 1 game panel
- 1 counter
- 1 rope bridge

Posts:

Steel pipes \varnothing 101.6 mm (0'-4"); wall thickness 4 mm (0'-1") with a round cast aluminum post top; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; Cross tubes - stainless steel Framework-®tubes, \varnothing 48 mm (0'-2")

Nodes:

Framework-®aluminum ball connectors, \varnothing 200 mm (0'-8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM-caps

Panels/Ramp:

HDPE-panel (roofs and walls), thickness 19 mm (3/4"), panel connected to steel pipes (for more details, see members) with cast aluminum panel clamps; non-skid HPL-panel (bottoms and ramp), thickness 19 mm (3/4")

Ropes:

U-Rope®-round strand ropes with galvanized steel cores, \varnothing 16mm (5/8") – unless otherwise noted; external strands are covered with non-abrasive UV-resistant Polyester-yarn

Rope Bridge:

Rope \varnothing 16mm (5/8"), narrow mesh size; Rope crossing points localized by durable, drop forged aluminum-balknests (no plastic)

Connections:

Number of mechanical components as less as possible; all bolts and nuts exposing permanently to the weather consist of stainless steel

Stepladder:

non-skid HPL-tiles (steps), thickness 19 mm (3/4"); curved stainless steel handrails

Slide:

Rectangular stainless steel slide, narrow type width 0.46m (1'-7"); side profile with stainless steel split tubes (sharpened and polished); access height 0.90m (2'-12")


Berliner

Berliner Seilfabrik
Play Equipment Corporation
96 Brookfield Oaks Drive, Suite 140
Greenville, SC 29607

T + 1 864 627 1092
F + 1 864 627 1178

www.berliner-playequipment.com
info@berliner-seilfabrik.com

