UFO.M2 – Product Specification



UFOs – Spatial nets in pentagonal Frameworx frames With the UFOs, children of all ages can explore play and climb galaxies where no children have gone before – for even more fun and adventure.

The compact UFOs can be combined to produce larger and more complex fleets.

At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487: UFOs 90.220.020 5+ 2.12 m (7'-0") 5.7 m x 3.4 m x 2.2 m (18'-7" x 11'-1" x 7'-0") 8.7 m x 6.4 m 9.4 m x 7.1 m (30'-7" x 23'-1") 43.9 m² 52.2 m² (561.9 sf) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee: Certificate according to DIN EN 1176: 6 pc. 1,8 m³ (63.6 ft³) 2 5 hours Ø 0.1 x 5.8 m (Ø 0'-4" x 19'-0") 30 kg (66.1 lbs) 2,5 m³ (88.3 ft³) Lifelong No.: Z2.16.01.10256.249 TÜV Product Service





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

www.berliner-playequipment.com info@berliner-seilfabrik.com

UFO.M2 – Product Specification





Technical Data.

The following text can also be used for tenders.

UFO.M2 (5.7 m x 3.4 m x 2.2 m / 18'-7" x 11'-1" x 7'-0") with TÜV-certificate according to DIN EN 1176 and 10-years warranty-certificate consists of the following elements:

Members:

Stainless steel Frameworx.®tubes, \varnothing 60.3 mm (2 3/8''); wall thickness 2.0 mm (3/32"), material AISI304 (DIN 1.4301).

Nodes:

Frameworx-aluminum ball connectors, \varnothing 250mm (9-13/16''); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system, securely closed with durable ebonite caps.

Ropes:

U-Rope-round strand ropes with steel cores, []6mm (5/8") with galvanized wires, external strands are covered with non-abrasive UV-resistant Polyester-yarn. Maximum breaking stress 115kN.

Spatial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required).





Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

www.berliner-playequipment.com info@berliner-seilfabrik.com