UFO.M3 – Product Specification



UFOs - Spatial nets in pentagonal Frameworx frames

With the UFOs, children of all ages can explore play and climb galaxies where no children have gone before – for even more fun and adventure.

The compact UFOs can be combined to produce larger and more complex fleets.

At a glance.

Product Family: Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487:

UFOs 90.220.030 1.93 m (6'-4") 5.0 m x 5.7 m x 2.2 m (16'-2" x 18'-7" x 7'-0") 8.0 m x 8.7 m 8.6 m x 9.4 m (28'-2" x 30'-7")

 $52.2\,m^2$ 61.2 m² (658.8 sf)

Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Revision: April 2016

Certificate according to DIN EN 1176:

1.8 m³ (63.6 ft³)

6 hours Ø 0.1 x 1.8 m (Ø 0'-4" x 5'-11") 30 kg (66.1 lbs) 3.7 m³ (130.7 ft³)

Lifelong


No.: Z2.16.01.10256.249 **TÜV Product Service**




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1864 627 1092 F + 1 864 627 1178

UFO.M3 – Product Specification





Technical Data.

The following text can also be used for tenders.

UFO.M3 ($5.0 \text{ m} \times 5.7 \text{ m} \times 2.2 \text{ m} / 16'-2'' \times 18'-7'' \times 7'-0''$) with TÜV-certificate according to DIN EN 1176 and 10-years warranty-certificate consists of the following elements:

Members:

Stainless steel Frameworx- $^{\circ}$ tubes, \varnothing 60.3 mm (2 3/8"); wall thickness 2.0 mm (3/32"), material AISI304 (DIN 1.4301).

Nodes:

Frameworx-aluminum ball connectors, \varnothing 250mm (9-13/16''); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system, securely closed with durable ebonite caps.

Ropes

Revision: April 2016

U-Rope-round strand ropes with steel cores, \$_\mathbb{M}\text{fmm (5/8")}\$ with galvanized wires, external strands are covered with non-abrasive UV-resistant Polyester-yarn. Maximum breaking stress 115kN.

Spatial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required).





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178