VIP Swing - Product Specification



HodgePodge - A variety of study and durable sport and play elements

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities.

Climbing trees, a Wasp's nest, Volleyball nets for sporting activities, cable rides for fun and excitement.

VIP Swing - At a glance.

Product Family:

Item Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required ASTM 1487:

Minimum space required DIN EN 1176:

HodgePodge 97.100.026

2.20 m (7'-3") $4.7 \, \text{m} \, \text{x} \, 2.0 \, \text{m} \, \text{x} \, 3.5 \, \text{m}$ (15'-4" x 6'-7" x 11'-6") 7.7 m x 9.2 m

Revision: April 2016

8.4 m x 9.8 m (27'-5" x 32'-2")

53.6 m² 62.6 m² (673.8 sf) Number of Foundations: Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume: Spare part guarantee:

Certificate according to EN 1176:

2 1.4 m³ 3 hours Ø 0.1 m x 4.5 m

(Ø 0'-4" x 14'-9") 175 kg (385 lbs) 0.7 m3 (24.7 ft3)

Lifelong


No.: Z2.16.01.10256.259 **TÜV Product Service**



Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1864 627 1092 F + 18646271178

VIP Swing - Product Specification





Technical Data.

The following text can also be used for tenders.

Steel posts Jan:

Steel pipes \varnothing 133 mm (5 ¼") with rounded cast aluminum post top, minimum wall thickness 7,1mm (1/4"): anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

Terranos clamps:

Two-part cast a uminum connecting clamps for the height-adjustable connection of rope elements or steel pipes to Terranos steel posts.

Ropes:

U-Rope-round strand ropes with steel cores, \varnothing 16mm (5/8") – unless otherwise noted; with galvanized wires, external strands covered; with non-abrasive UV-resistant Polyester-yarn.

Spreader bar:

1 Frameworx-304 stainless steel pipe, Ø 60.3 mm (2 3/8");

Steel pipe:

1 Frameworx-steel pipe, \varnothing 60.3 mm (2 3/8"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process.

Nodes:

Revision: April 2016

2 Frameworx-aluminum ball connectors, \varnothing 200mm (7-7/8"); anticorrosion treatment and color finish: sandblasting and zinc-/ epoxy-/ polyester-process; securely closed with durable ebonite caps.





Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178