# Cosmo.10 - Product Specification



### Cosmo - The first totally round rope play structure

The innovative space structure offers exciting play options never before experienced. Cosmo is a whole new round of fun in play equipment: The first totally round rope play structure has arrived.

Apart from the basic system, Cosmo stands out due to its many freely selectable add-ons and diverse play activities. This gives the Cosmo an advantage over several rounds compared to conventional climbing frames.

In 2008 Cosmo received the prestigious "Red Dot" design award for excellent design quality.

78.8 m<sup>2</sup>

76.9 m<sup>2</sup> (827.7 sf)

## Cosmo.10 -At a glance.

Number of Foundations: Product Family: Cosmo 5 pc. 90.112.100 Item Number: Concrete Volume C20/C25: 1.5 m3 (53.0 ft3) Children's Age: Number of skilled installers required: Fall Height (DIN EN 1176): Installation Time without foundation: 2.30 m (7'-7") 7 hours Length x Width x Height: 8.4 m x 6.0 m x 3.8 m Dimensions of largest part: 0.1 m x 1.3 m x 4.6 m (0'-4" x 4'-3" x 15'-1") (27'-5" x 19'-9" x 12'-4") Protective Surfacing Area (DIN EN 1176): 12.2 m x 9.7 m Weight of heaviest part: 105 kg (231.5 lbs) Protective Surfacing Area (ASTM 1487):  $12.2 \, \text{m} \, \text{x} \, 10.0 \, \text{m}$ Shipping Volume: 4.0 m<sup>3</sup> (141.3 ft<sup>3</sup>) (40'-0" x 32'-8") Spare part guarantee: Lifelong Minimum space required DIN EN 1176:





Minimum space required ASTM 1487:

Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com Revision: March 2016 www.berliner-seilfabrik.com Page 1

# Cosmo. 10 - Product Specification





#### Technical Data.

The following text can also be used for tenders.

- Cosmo
- Banister
- Duck Jibe

## Tube framework:

Curved stainless steel tubes; Ø 60.3 mm (2 3/8")

#### Nodes:

Frameworx-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

#### Ropes

U-Rope®-round strand ropes with galvanized and covered wires; external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene): Ø 16 mm (5/8")

## Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situreplaceable rope strands (no special tools required)

#### Duck Jibe:

Curved Frameworx stainless steel pipes Ø 60.3 mm (2 3/8"), wall thickness 2.9 mm; lubricated, antifriction reciprocal bearings; connected to the main Cosmo framework with a thick-walled Frameworx-aluminum ball connector, Ø 250mm (9-13/16"), standing platform is comprised of grained HDPE, 19 mm thick; the turning bearing construction located in the ground consists of Frameworx stainless steel pipe retainers, Ø 40 mm (1-3/5"), wall thickness 5 mm (3/16")

### **Curved banister:**

Curved stainless steel pipes;  $\emptyset$  60.3 mm (2 3/8") wall thickness 2.9 mm; connected to the main structure with 2 aluminum ball connectors  $\emptyset$  200mm (7-9/10")





Tel. +49.(0)30.41 47 24-0 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com www.berliner-seilfabrik.com