

Tower7 – Product Specification



Illustration shows Combination of elements.


Tower7

This mysterious tower can be climbed via plate-shaped nets. Four meters above ground level, an angled reclining surface invites visitors to relax and also offers commanding views over the valleys below.

Tower7 – at a glance.

Product Family:	Greenville	Number of Foundations:	Upon request
Item Number:	90.295.007	Concrete Volume C20/C25:	Upon request
Children's Age:	5+	Number of skilled installers required:	Upon request
Fall Height (DIN EN 1176):	-	Installation Time without foundation:	Upon request
Length x Width x Height:	4.8 m x 4.8 m x 10.8 m (15'-9" x 15'-9" x 35'-6")	Dimensions of largest part:	Upon request

The protective Surfacing Area and Fall Height of our Towers & Triis depend on the chosen combination and execution and be like calculated on request you.




Berliner
 Berliner Seilfabrik GmbH & Co.
 Lengeder Straße 2/4
 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
 www.berliner-seilfabrik.com



Tower7 – Product Specification



Technical Data.

The following text can also be used for tenders.

Posts:

Steel posts \varnothing 133 mm (5 1/4"); wall thickness 5 - 11 mm (3/16" - 3/8") with a round cast aluminum post top; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Tube framework:

Stainless steel tubes; \varnothing 60.3 mm (2 3/8"); connected to the posts with Terranos two-part cast aluminum connecting clamps; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Nodes:

Framework[®]-aluminum ball connectors; \varnothing 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTEM TT net tensioning system; securely closed with durable EPDM- caps

Ropes:

U-Rope[®]-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene)

Spacial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required)

Bamboo panels:

Bamboo strips 90 mm, (3 1/2") mounted at a particle board made from HDPE, 19 mm (3/4") thickness, rounded edges, mounted with aluminum plate clamps to the tubes of the framework

