

Univers

Cosmo.10 Product Specifications



Published: November 2020



Cosmo.10

The first totally spherical rope play structure offers exciting play options. Cosmo is a whole new round of fun in play equipment. Apart from the basic system, Cosmo stands out due to its many freely selectable add-ons and diverse play activities.

For windsurfers, the Duck Jibe is one of the coolest old school moves. The Cosmo is designed for turbulent fun and energetic play. Besides the banister, the Duck Jibe is the attraction of the Cosmo.10.

90.112.100

Product Family	Univers
Length x Width x Height (m) Length x Width x Height ("'-")	8,4 x 6,0 x 3,8 27-5 x 19-9 x 12-4
Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("'-")	12,2 x 9,8 12,2 x 10,0 40-0 x 32-8
Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("'-")	2,30 7-7
Age	5
Minimum Space required acc. to DIN EN 1176 (m ²) Minimum Space required acc. to ASTM 1487 (ft ²)	78,7 827,7
Number of Foundations	5
Concrete Volume C20/C25 (m ³)	1,7
Number of skilled Installers required	2-3
Installation Time without Foundation	8 hours
Dimensions of largest Part (m)	On request
Weight of heaviest Part (kg)	120
Shipping Volume (m ³)	On request
Total Weight (kg)	On request
Spare Part Guarantee	Lifelong



Technical Data

Technical changes are reserved. The following text can also be used for tenders.

Included Products:

- Duck Jibe
- Banister

Tubes:

The bent steel tubes with a diameter of Ø 60,3 mm (2 3/8") and wall thicknesses of 2 mm (1/16") till 10 mm (3/8") are thermally galvanised to protect against corrosion and powder-coated in colour using a solvent-free epoxy-polyester-process or consist of stainless steel.

Balls:

The Framework[®] aluminium balls with a diameter of 250 mm (9 13/16") are sandblasted and powder-coated solvent-free to protect against corrosion. In addition, they are equipped with the internal, patented AstemTT[®] tensioning system and securely closed with durable EPDM caps.

Ropes:

The U-Rope[®] with strand cores and rope core made of galvanised wires has outer strands which are covered with highly abrasion-resistant and highly UV-resistant polyester yarn (not polypropylene). The rope diameter is Ø 16 mm (5/8").

Spatial Net:

The net structures are fixed at the rope crossing points by durable aluminium parts such as cloverleaf ring, forged ball knot, T-connectors and barrel-ferrule (no plastic). Spatial nets are low in follow-up costs due to individually replaceable rope strands.

Curved Banister:

The curved Framework[®] stainless steel tubes with a diameter of Ø 60,3 mm (2 3/8") and a wall thickness of 2,9 mm (1/8") are connected to the main frame by aluminium balls with a diameter of 200 mm (7 7/8").

Duck Jibe:

The Framework[®] stainless steel tubes are connected at the top to the main framework by lubricated, antifriction reciprocal bearings and an aluminium Ball connector. The standing platform is comprised of grained HDPE and the bearing construction to the ground consists of a steel pipe retainer.