



Product Service

# CERTIFICATE

No. Z2 010256 0300 Rev. 00

**Holder of Certificate:** **Berliner Seilfabrik GmbH & Co.**

Lengeder Straße 4  
13407 Berlin  
GERMANY

**Certification Mark:**



**Product:** **Swings**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713178716-04

**Valid until:** 2026-04-26

**Date,** 2021-04-30

( Jens Biesenack )

# CERTIFICATE

No. Z2 010256 0300 Rev. 00

## Model(s):

**90.260.534 Arch Swing**  
**90.260.532 Bowl Swing**  
**90.260.531 Cup Swing**  
**90.260.520 Face-to-Face Swing**  
**97.100.025 Cloud 9**  
**95.190.320 Double Palmetto Saucer**  
**95.190.263 Palmetto Saucer**  
**90.260.510 Sky Swing**  
**90.340.049 Double Swingo.2.2**  
**95.171.311 Double Cloud 9**  
**90.160.140 Swingo.01**  
**90.160.141 Swingo.02**  
**90.160.150 Swingo.03**  
**90.160.151 Swingo.04**  
**90.340.004 Triple Swingo**  
**90.260.501 Swingo.2.1**  
**90.260.502 Swingo.2.2**  
**90.260.503 Swingo.2.3**  
**90.260.504 Swingo.2.4**  
**97.100.026 VIP Swing**

## Parameters:

Stainless steel tube, Ø60.3 mm and straight or curved steel post Ø101.6 mm or Ø133 mm, Framework® aluminium spheres; Ø250 mm; sandblasted and anti-corrosion protecting, solvent free in zinc-epoxy-polyester stove method, coloured powder coated; internal fastening, closed off with EPDM seals, closed off with rounded aluminium caps.

Nest swing seat made of galvanised tubular steel ring, sheathed with impact absorbing material and wound around with impact absorbing fibre rope.

Close-meshed net made of steel rope has steel wire stands, which are sheathed with braided polyester yarns.

The connecting parts are made of stainless steel (V2A).

Nest swing suspension elements made of U-Rope® round stranded rope with strands and rope core made of galvanised steel wires, the outer strands are sheathed with polyester yarn (no polypropylene). Rope diameter Ø16 mm, connected to universal swing joints with stainless steel chains.

Black rubber safety swing seat pivot supported on the cross tube and fixed in polyamide sockets.

# CERTIFICATE

No. Z2 010256 0300 Rev. 00

- 90.260.534 Arch Swing  
Dimensions (L x W x H): 1.3 x 3.6 x 3.2 m
- 90.260.532 Bowl Swing  
Dimensions (L x W x H): 1.3 x 3.7 x 2.9 m
- 90.260.531 Cup Swing  
Dimensions (L x W x H): 1.3 x 3.7 x 2.9 m
- 90.340.049 Double Swingo.2.2  
Dimensions (L x W x H): 1.8 x 7.2 x 2.5 m
- 95.171.311 Double Cloud 9  
Dimensions (L x W x H): 6.25 x 1.20 x 2.00 m
- 90.260.520 Face-to-Face Swing  
Dimensions (L x W x H): 6.8 x 5.9 x 3.1 m
- 97.100.025 Cloud 9  
Dimensions (L x W x H): 3.3 x 1.3 x 2.1 m
- 95.190.320 Double Palmetto Saucer  
Dimensions (L x W x H): 5.7 x 1.0 x 2.2 m
- 95.190.263 Palmetto Saucer  
Dimensions (L x W x H): 3.0 x 1.0 x 2.2 m
- 90.260.510 Sky Swing  
Dimensions (L x W x H): 0.3 x 2.6 x 4.9 m
- 90.160.140 Swingo.01  
Dimensions (L x W x H): 2.41 x 1.7 x 2.13 m
- 90.160.141 Swingo.02  
Dimensions (L x W x H): 3.8 x 1.7 x 2.13 m
- 90.160.150 Swingo.03  
Dimensions (L x W x H): 4.6 x 2.5 x 3.1 m
- 90.160.151 Swingo.04  
Dimensions (L x W x H): 5.9 x 2.5 x 3.1 m
- 90.260.501 Swingo.2.1  
Dimensions (L x W x H): 2.5 x 1.7 x 2.3 m
- 90.260.502 Swingo.2.2  
Dimensions (L x W x H): 3.8 x 1.7 x 2.5 m
- 90.260.503 Swingo.2.3  
Dimensions (L x W x H): 4.6 x 2.5 x 3.2 m



# CERTIFICATE

No. Z2 010256 0300 Rev. 00

90.260.504 Swingo.2.4  
Dimensions (L x W x H): 5.9 x 2.5 x 3.4 m

90.340.004 Triple Swingo  
Dimensions (L x W x H): 1.7 x 10.80 x 2.1 m

97.100.026 VIP Swing  
Dimensions (L x W x H): 4.7 x 2.0 x 3.5 m

**Tested  
according to:**

EN 1176-1:2017  
EN 1176-3:2017