
Spirelli.01

HodgePodge



Published: June 2023

Spirelli.01 Product Specification

HodgePodge Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All HodgePodge Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminum connectors, high density polyethylene (HDPE) panels and ITR-bearings for maximum safety and durability. This sculptural looking noodle is a climbing pole if you want it to be. Almost like a piece of art to play with. Who said that a climbing pole must be straight?



Spirelli.01

(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	Product Family	HodgePodge
	$\label{eq:length} \begin{split} & \text{Length} \times \text{Width} \times \text{Height (m)} \\ & \text{Length} \times \text{Width} \times \text{Height ('-'')} \end{split}$	0,3 × 0,3 × 2,9 1-0 × 1-0 × 9-6
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-'')	3,3 × 3,3 4,0 × 4,0 13-0 × 13-0
000↓	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-")	1,4 4-7
\mathbb{C}	Age	5
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	8,4 131,0
$\Diamond^{\diamondsuit} \diamond$	Number of Foundations	1
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	0,4 14,2
	Number of skilled Installers required	2
	Installation Time without Foundation	2 hours
		3,3 × 0,3 × 0,3 10-10 × 1-1 × 1-0
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	40 89
	Shipping Volume (m³) Shipping Volume (ft³)	0,8 23,3
ĩĩĩ	Total Weight (kg)	85
	Total Weight (lbs)	188

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.

The following text can also be used for tenders.

Sphere:

Frameworx[®]- aluminum ball connector, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with a durable EPDM-cap.

Tube:

Bent Frameworx®- stainless steel tube Ø 60,3 mm (2 3/8"), wall thicknesses 2,9 mm (1/8"), smoothed and brushed / polished.





1:200