

Swingo.02

HodgePodge



Published: May 2024
















Swingo.02

Product Specification


HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, Wasps' nest, zip lines, swings and carousels for fun and excitement.

The Swingo.02 with two swing seats is the ideal choice for little adventurers! With only four posts and a low height, it's perfect for toddler seats. Safe swinging fun guaranteed!

90.160.141

	Product Family	HodgePodge
	Length x Width x Height (m) Length x Width x Height ("")	3,8 x 1,7 x 2,2 12-5 x 5-7 x 7-0
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	7,2 x 3,1 8,0 x 7,5 26-3 x 24-5
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	1,17 6-5
	Age	3
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	22,2 502,6
	Number of Foundations	4
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	0,5 17,7
	Number of skilled Installers required	2
	Installation Time without Foundation	3 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("")	3,2 x 0,1 x 0,1 10-6 x 0-4 x 0-4
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	35 78
	Shipping Volume (m³) Shipping Volume (ft³)	1,1 38,8
	Total Weight (kg) Total Weight (lbs)	180 397
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.



1:200

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Tubes:

Steel tubes, Ø 60,3 mm (2 3/8"). Anticorrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process.

Swing Seat:

The durable black ebonite seat is hanging on a stainless steel chain with pivot bearings fixed to the horizontal pipe in maintenance-free PA-bushes.

Spheres:

Framework®- aluminum ball connectors, Ø 250 mm (9 13/16"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with durable EPDM-caps.