

Cat Tail.03

HodgePodge



Published: February 2024

Cat Tail.03
















Product Specification


HodgePodge Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All HodgePodge Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminium connectors, high density polyethylene (HDPE) panels and ITR-bearings for maximum safety and durability.

The Cat Tail has a body and a stem made of stainless steel. The curved stem and the bi-coloured HDPE platform turn a piece of play equipment into an eye-catcher for all public places in town.

Cat Tail.03

90.260.203

| | | |
|--|--|--|
|  | Product Family | HodgePodge |
|  | Length x Width x Height (m) Length x Width x Height ("") | 0,6 x 0,6 x 1,9 2-0 x 2-0 x 6-1 |
|  | Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("") | 3,6 x 3,6 4,3 x 4,3 14-0 x 14-0 |
|  | Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("") | 0,40 1-4 |
|  | Age | 5 |
|  | Minimum Space required acc. to DIN EN 1176 (m ²) Minimum Space required acc. to ASTM 1487 (ft ²) | 10,2 153,3 |
|  | Number of Foundations | 1 |
|  | Concrete Volume C20/C25 (m ³) Concrete Volume C20/C25 (ft ³) | 0,5 18 |
|  | Number of skilled Installers required | 2 |
|  | Installation Time without Foundation | 2 hours |
|  | Dimensions of largest Part (m) Dimensions of largest Part ("") | 2.2 x 0.6 x 0.7 23.7 x 6.5 x 7.5 |
|  | Weight of heaviest Part (kg) Weight of heaviest Part (lbs) | 45 100 |
|  | Shipping Volume (m ³) Shipping Volume (ft ³) | 0,8 28,3 |
|  | Total Weight (kg) Total Weight (lbs) | 100 220.5 |
|  | Spare Part Guarantee | Lifelong |



1:200

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Turntable:

Antiskid HDPE panels, 19 mm (3/4"), bolted on the stainless steel substructure.

Tube:

Framework®- stainless steel tube.

Sphere:

Framework®- aluminum ball connector, Ø 200 mm (7 7/8"). Anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process. The ball incorporates an embedded fastening system. Securely closed with a durable EPDM-cap.