

Mini Jupiter – Product Specification



Univers – Classics among rope playground equipment

Net structures offer hours of fun and adventure on several levels – climbing and swinging, up and down, horizontally and vertically – space on earth.

The original spatial nets: Born over 40 years ago as a play concept, continuously further developed in form and detail, still popular even after several generations.

Mini Jupiter – at a glance.



Product Family:	Univers	Number of Foundations:	4 pc.
Item Number:	90.100.040	Concrete Volume C20/C25:	1.0 m³(35.3 ft³)
Children's Age:	5+	Number of skilled installers required:	2
Fall Height (DIN EN 1176):	1.23 m (4'-1")	Installation Time without foundation:	5 hours
Length x Width x Height:	3.6 m x 3.6 m x 3.7 m (11'-10" x 11'-10" x 12'-2")	Dimensions of largest part:	ø 0.1 m x 1.5 m (ø 0'-4" x 4'-11")
Protective Surfacing Area (DIN EN 1176):	6.6 m x 6.6 m	Weight of heaviest part:	120 kg (264.6 lbs)
Protective Surfacing Area (ASTM 1487):	7.3 m x 7.3 m (23'-10" x 23'-10")	Shipping Volume:	2.5 m³ (88.3 ft³)
Minimum space required DIN EN 1176:	41.3 m²	Spare part guarantee:	Lifelong
Minimum space required ASTM 1487:	49.4 m² (531.7 sf)	Certificate according to DIN EN 1176:	No.: Z2 16 01 10256 241 TÜV Product Service


Berliner
 Berliner Seilfabrik GmbH & Co.
 Lengeder Straße 2/4
 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
 www.berliner-seilfabrik.com

Mini Jupiter – Product Specification



M 1:200

Technical Data.

The following text can also be used for tenders.

Tube framework:

Framework-steel tubes, \varnothing 60.3 mm (2 3/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Nodes:


Framework-aluminum ball connectors; \varnothing 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; incorporating an ASTM TT net tensioning system; securely closed with durable EPDM- caps

Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter \varnothing 16 mm (5/8")

Spatial netting:

Rope crossing points are localized with durable, forged aluminum-alloy cloverleaf rings and forged aluminum-alloy ballknots (no plastic connections); in situ-replaceable rope strands (no special tools required)




Berliner
Berliner Seilfabrik GmbH & Co.
Lengeder Straße 2/4
D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
www.berliner-seilfabrik.com

Revision: March 2016

Page 2