Side-by-Side Swing

HodgePodge



Published: February 2024

Side-by-Side Swing Product Specification

HodgePodge Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All HodgePodge Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminum connectors, high density polyethylene (HDPE) panels and ITR-bearings for maximum safety and durability. Swinging together is still the most fun, whether on classic seats or in the cool nest swing. And due to the low entry height of the nest swing, even the little ones will get the most fun out of swinging.




Side-by-Side Swing

90.340.055

+ 	Product Family	HodgePodge
	Length \times Width \times Height (m) Length \times Width \times Height ('-")	1,6 × 6,8 × 3,1 5-3 × 22-2 × 9-11
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-")	8,1 × 6,8 9,8 × 10,5 32-0 × 34-2
0 0 ↓	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-")	1,44 8-1
́рО́	Age	2-12
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	51,3 809,0
$\diamond \diamond \diamond$	Number of Foundations	3
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	1,8 63,6
	Number of skilled Installers required	2
(1)	Installation Time without Foundation	8 hours
<pre></pre>	Dimensions of largest Part (m) Dimensions of largest Part ('-")	2,9 × 0,5 × 0,2 9-7 × 1-5 × 0-8
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	100 220
<u> </u>	Shipping Volume (m³) Shipping Volume (ft³)	4,4 155,4
	Total Weight (kg) Total Weight (lbs)	660 1455
\bigcirc	Spare Part Guarantee	Lifelong





The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved. The following text can also be used for tenders.