

Published: February 2020

Wonderwalls.01

Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned out around a central post.

As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches, sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.


The highlight of Wonderwalls.01 in the design of a tree stump is a passage with rubber membranes connecting two play areas. And anyone looking closely will find a secret opening under the bench.



Wonderwalls.01

Published: February 2020

90.295.700.1	
Product Family	Spooky Rookies
Length x Width x Height (m) Length x Width x Height ('-'')	2,3 x 2,7 x 1,6 7-7 x 8-11 x 5-0
Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-'')	5,3 x 5,7 6,0 x 6,4 19-7 x 20-11
Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ('-")	0,94 4-10
○ ○ Age	3
Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	20,95 287,8
Number of Foundations	5
Concrete Volume C20/C25 (m³)	0,63
Number of skilled Installers required	2
Installation Time without Foundation	8 hours
□ Dimensions of largest Part (m)	1,5 x 1,2
Weight of heaviest Part (kg)	40
Shipping Volume (m³)	On request
급급 Total Weight (kg)	On request
Spare Part Guarantee	Lifelong





Technical Data

The following text can also be used for tenders.

Included Products:

- Rubber Membrane Curtain
- Puzzle Elements
- Mud Tables
- Rotating Disc

Tubes

The Steel tubes with a diameter of Ø 60,3 mm (2%) and a wall thickness of 2,9 mm (%) are thermally galvanised to protect against corrosion and powder-coated in colour using a solvent-free epoxy/polyester/process. They are also watertight closed with rounded aluminium caps.

Panels:

Wall, play and design elements are made of solid-coloured and grained HDPE panels with a thickness of 19 mm (3/4") and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminium panel clamps.

Rubber Membrane:

The rubber mat strips are made of durable and vandal-proof conveyor belt.