

# Spooky Rookies

Wonderwalls.02 Product Specification



Published: August 2021

## Wonderwalls.02
















Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned out around a central post.


As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches,

sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

Toddlers can immerse themselves in the world of wonders and fables at Wonderwalls.02, like pixies. Play elements such as mud tables, hatches in the walls and a sand workshop encourage role play. A hammock made of rubber mats encourages the youngsters to swing or try their first walking and crawling experiences on shaky ground.

## 90.295.700.2

	Product Family	<b>Spooky Rookies</b>
	Length x Width x Height (m) Length x Width x Height ("")	<b>5,0 x 2,7 x 1,7</b> <b>16-5 x 8-11 x 5-6</b>
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	<b>8,0 x 5,7</b> <b>8,7 x 6,4</b> <b>28-5 x 20-11</b>
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	<b>1,26</b> <b>4-2</b>
	Age	<b>2-5</b>
	Minimum Space required acc. to DIN EN 1176 (ft²) Minimum Space required acc. to ASTM 1487 (ft²)	<b>30.1</b> <b>402.9</b>
	Number of Foundations	<b>6</b>
	Concrete Volume C20/C25 (ft³)	<b>42.4</b>
	Number of skilled Installers required	<b>2</b>
	Installation Time without Foundation	<b>8 hours</b>
	Dimensions of largest Part ("")	<b>4-11 x 3-11</b>
	Weight of heaviest Part (lbs)	<b>88.2</b>
	Shipping Volume (ft³)	<b>On request</b>
	Total Weight (lbs)	<b>On request</b>
	Spare Part Guarantee	<b>Lifelong</b>



### Technical Data

Technical changes are reserved. The following text can also be used for tenders.

#### Included Products:

- Revolving Flaps
- Ramp
- Sand Slide
- Sand Crane
- Rubber Hammock

#### Posts:

The steel posts with a diameter of Ø 5 ¼" are thermally galvanized to protect against corrosion or, if desired, can be powder-coated in color using a solvent-free epoxy/polyester/process. They are also sealed watertight with rounded aluminum caps.

#### Tubes:

The Steel tubes with a diameter of Ø 2 ¾" and a wall thickness of ⅛" are thermally galvanized to protect against corrosion and powder-coated in color using a solvent-free epoxy/polyester/process. They are also watertight closed with rounded aluminum caps.

#### Terranos Clamps:

For height-adjustable connection of the ropes to the steel posts the two-part Terranos® aluminum clamps are used in conjunction with shackle connections.

#### HDPE-Panels:

Wall, play and design elements are made of solid-colored and grained HDPE panels with a thickness of ¾" and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminum panel clamps.

#### Ropes:

The U-Rope® with strand cores and rope core made of galvanized wires has outer strands which are covered with highly abrasion-resistant and highly UV-resistant polyester yarn (not polypropylene).

#### Rubber Mat:

The rubber mat is made of durable and vandal-proof conveyor belt.