

Spooky Rookies

Wonderwalls.02 Product Specification



Published: June 2022

Wonderwalls.02





















Fitted with a wealth of play functions in a reduced space Wonderwalls are specifically aimed at the needs of toddlers and pre-school children. Each equipment design offers a number of play worlds that are interconnected by windows and passages between the three or respectively four walls, which are fanned out around a central post.

As well as space for retreat, children are encouraged to engage in role-playing games using elements such as mud tables, benches,

sand workshops or openings in the walls. Language and social skills are fostered and trained in a playful way.

Toddlers can immerse themselves in the world of wonders and fables at Wonderwalls.02, like pixies. Play elements such as mud tables, hatches in the walls and a sand workshop encourage role play. A hammock made of rubber mats encourages the youngsters to swing or try their first walking and crawling experiences on shaky ground.

90.295.700.2

 Product Family	Spooky Rookies
 Length x Width x Height (m)	5,0 x 2,7 x 1,7
 Length x Width x Height (ft-in)	16-5 x 8-11 x 5-6
 Protective Surfacing Area acc. to DIN EN 1176 (m)	8,0 x 5,7
 Protective Surfacing Area acc. to ASTM/CSA (m)	8,7 x 6,4
 Protective Surfacing Area acc. to ASTM/CSA (ft-in)	28-5 x 20-11
 Fall Height acc. to EN 1176 (m)	1,26
 Fall Height acc. to ASTM/CSA (ft-in)	4-2
 Age	3
 Minimum Space required acc. to DIN EN 1176 (m ²)	30,1
 Minimum Space required acc. to ASTM 1487 (ft ²)	402,9
 Number of Foundations	6
 Concrete Volume C20/C25 (m ³)	1,2
 Number of skilled Installers required	2
 Installation Time without Foundation	8 hours
 Dimensions of largest Part (m)	1,5 x 1,2
 Weight of heaviest Part (kg)	40
 Shipping Volume (m ³)	On request
 Total Weight (kg)	On request
 Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

Technical Data

Technical changes are reserved. The following text can also be used for tenders.

Included Products:

- Revolving Flaps
- Ramp
- Sand Slide
- Sand Crane
- Rubber Hammock

Posts:


The steel posts with a diameter of Ø 133 mm (5 ¼") are thermally galvanised to protect against corrosion or, if desired, can be powder-coated in colour using a solvent-free epoxy/ polyester/ process. They are also sealed watertight with rounded aluminium caps.

Tubes:

The Steel tubes with a diameter of Ø 60,3 mm (2 ¾") and a wall thickness of 2,9 mm (1/8") are thermally galvanised to protect against corrosion and powder-coated in colour using a solvent-free epoxy/polyester/process. They are also watertight closed with rounded aluminium caps.

Terranos Clamps:

For height-adjustable connection of the ropes to the steel posts the two-part Terranos® aluminium clamps are used in conjunction with shackle connections.



HDPE-Panels:

Wall, play and design elements are made of solid-coloured and grained HDPE panels with a thickness of 19 mm (¾") and form milled. All edges are rounded off and the walls are connected to the pipes with cast aluminium panel clamps.

Ropes:

The U-Rope® with strand cores and rope core made of galvanised wires has outer strands which are covered with highly abrasion-resistant and highly UV-resistant polyester yarn (not polypropylene).

Rubber Mat:

The rubber mat is made of durable and vandal-proof conveyor belt.