

Spooky Rookies

Roo M.02 Product Specification



Published: November 2019

















Roo.M02


Spooky Rookies promote physical development. During climbing, sliding and romping in the many different playhouses, toddlers are able to test their skills.

It is possible to combine the playhouses' shape, size and colors. A stepladder, ramp or slide offer further constructive options.

The appeal of this small Greenville-style playhouse Roo.M02 derives from its design and functionality. The flat climbing net with accompanying rope handrail poses an exciting challenge for beginners to the world of climbing, while the Play-Panel and mud table encourage role-play.

90.295.600.2

	Product Family	Spooky Rookies
	Length x Width x Height (m) Length x Width x Height ("")	2,1 x 4,9 x 2,1 6-11 x 15-10 x 6-10
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	5,1 x 8,4 5,8 x 8,5 18-11 x 27-10
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	0,9 3-0
	Age	2-5
	Minimum Space required acc. to DIN EN 1176 (m ²) Minimum Space required acc. to ASTM 1487 (ft ²)	31.8 427.33
	Number of Foundations	7
	Concrete Volume C20/C25 (ft ³)	28.25
	Number of skilled Installers required	2
	Installation Time without Foundation	8 hours
	Dimensions of largest Part ("")	8-6 x 4-3 x 1-11
	Weight of heaviest Part (lbs)	121.25
	Shipping Volume (ft ³)	On request
	Total Weight (lbs)	On request
	Spare Part Guarantee	Lifelong
	Certified acc. to EN 1176	Nr.: Z2 18 05 10256 275



Technical Data

The following text can also be used for tenders.

Included Products:

- Haunted house
- Access Net
- Slide
- Play panel

Posts:

Steel pipes Ø 4"; wall thickness 3/16" with a round cast aluminum post top; anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process; Cross tubes – stainless steel Frameworx®-tubes, Ø 1 7/8"

Balls:

Frameworx®-aluminum ball connectors, Ø 7 7/8"; anti-corrosion treatment and color finish: sandblasting and solvent-free epoxy-/ polyester-process; securely closed with durable EPDM-caps.

Panels:

HDPE-panel (roof and walls), thickness 3/4"; panel connected to steel pipes (for more details, see posts) with cast aluminum panel clamps; non-skid HPL-panel (bottom and ramp), thickness 3/4", except bent side panels with a thickness of 25/64".

Connections:

Number of mechanical components as less as possible; all bolts and nuts exposing permanently to the weather consist of stainless steel

Slide:

Rectangular stainless steel slide, narrow type width 1'-6 1/8"; side profile with stainless steel split tubes (smoothed and polished); access height 2'-11 7/16"

Access Net:

Rope Ø 5/8", mesh size 11 13/16" x 11 13/16", rope crossing points localized by durable, drop forged aluminum-ballknots (no plastic)