

# HodgePodge

## Cloud 9 Product Specifications


















Published: August 2021


### Cloud 9

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. A calisthenics system for sport activity, climbing trees, Wasps' nest, zip lines, swings and carousels for fun and excitement.

Our Cloud 9 is an accessible swing which allows several children at one time to fly "on the cloud".

## 97.100.025

	Product Family	<b>HodgePodge</b>
	Length x Width x Height (m) Length x Width x Height ("')	<b>3,3 x 1,3 x 2,1</b> <b>10-8 x 4-2 x 6-9</b>
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("')	<b>7,0 x 3,3</b> <b>7,5 x 7,0</b> <b>24-5 x 22-8</b>
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("')	<b>1,24</b> <b>6-2</b>
	Age	<b>2-12</b>
	Minimum Space required acc. to DIN EN 1176 (m <sup>2</sup> ) Minimum Space required acc. to ASTM 1487 (ft <sup>2</sup> )	<b>26,6</b> <b>333,7</b>
	Number of Foundations	<b>2</b>
	Concrete Volume C20/C25 (ft <sup>3</sup> )	<b>24.8</b>
	Number of skilled Installers required	<b>2</b>
	Installation Time without Foundation	<b>2 hours</b>
	Dimensions of largest Part ("')	<b>Ø 0-8 x 10-2</b>
	Weight of heaviest Part (lbs)	<b>154.4</b>
	Shipping Volume (ft <sup>3</sup> )	<b>45.9</b>
	Total Weight (lbs)	<b>749.6</b>
	Spare Part Guarantee	<b>Lifelong</b>



### Technical Data

Technical changes are reserved. The following text can also be used for tenders.

#### Posts:

The bent steel posts with a diameter of Ø 5 1/4" and a wall thicknesses of 1/4" are thermally galvanized to protect against corrosion and powder-coated in color using a solvent-free epoxy-polyester-process. In addition they are watertight sealed with rounded aluminum tops.

#### Balls:

Frameworkor<sup>®</sup>-aluminum ball connectors with a diameter of Ø 9 13/16". Anticorrosion treatment and color finish: sandblasted and powder-coated, securely closed with durable EPDM- caps.

#### Nest Swing Seat:

The nest swing seat is made of a galvanized steel tube ring, encased with shock-absorbing material and wrapped with a shock-absorbing fiber rope. The close-knit network of soft steel wire has strands covered with braided polyester yarns. The connection parts are made of stainless steel (V2A).

#### Suspension:

U-Rope<sup>®</sup>-round strand ropes with galvanized steel cores, external strands are covered with high abrasion-resistant and UV-resistant polyester-yarn (no Polypropylene). The diameter is Ø 3/8" and they are connected to the joint with steel chains.