

Calisthenics.05

HodgePodge


















Published: March 2024

Calisthenics.05

Product Specification

This small calisthenics facility can complement a playground well and is also a success for the adults: pull-ups and dangles with different distances.

95.190.713

	Product Family	HodgePodge
	Length × Width × Height (m) Length × Width × Height ("")	3,2 × 3,2 × 2,4 10-5 × 10-4 × 7-10
	Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ("")	* * *
	Fall Height acc. to EN 1176 (m) Fall Height acc. to ASTM/CSA ("")	* *
	Age	
	Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	* *
	Number of Foundations	3
	Concrete Volume C20/C25 (m³) Concrete Volume C20/C25 (ft³)	1,8 63,6
	Number of skilled Installers required	2
	Installation Time without Foundation	3 hours
	Dimensions of largest Part (m) Dimensions of largest Part ("")	0,2 × 0,9 × 2,4 0-8 × 2-12 × 7-11
	Weight of heaviest Part (kg) Weight of heaviest Part (lbs)	120 264,6
	Shipping Volume (m³) Shipping Volume (ft³)	9 315,6
	Total Weight (kg) Total Weight (lbs)	1050 2315
	Spare Part Guarantee	Lifelong

The dimensions of the equipment and protective surfacing area have been rounded up to one decimal digit.

* Safety areas as well as free fall height are determined according to a play equipment standard or relevant outdoor fitness standard, depending on the installation. Individual planning is necessary.

Technical Data

Technical changes are reserved.
The following text can also be used for tenders.

Tubes:

Framework®- steel tubes, Ø 168,3 mm (6 5/8"), wall thickness 10 mm (3/8"). Anti-corrosion treatment and color finish: sandblasting, solvent-free epoxy-/ polyester-process.

Horizontal Bars:

Comprised of stainless steel pipe Ø 40 mm (1-9/16"), wall thickness 5 mm (3/16").

